



## TP10-SE 12.5mm Transparent Indoor LED



## Specifications

LED Type	SMD3535
Cabinet Size(WXHXDmm)	600x600x70 mm
Cabinet Resolution	48x48 pixel
Module Quantity pcs/cabinet	4
Cabinet Pixels	2304 pixels
Installation type	Rental/Fixed
Average Power Consumption	150 watt/panel
Max. Power Consumption	250 watt/panel
Material Die-Cast	Alumunium
Cabinet Weight	8kg
Transparent	Yes (45%)
Flybar	60cm
Brightness	2400 nit
Colors	68 Billion
Driving Method	1/3
View Angle	Horizontal 120°, Vertical 120°
Min. Viewing Distance	12 meters
Brightness Control	Red,Green and Blue 256 Grade/Each
Fresh frequency	≥1920Hz
Frame Frequency	50 - 60Hz
Input Voltage	AC200-240V
Defects Rate	≤0.00001
Working Temperature (°C)	- 20~ + 40
Life span	≥50,000 hours
Module Brightness Uniformity	<3%
Gray Scale	65536
Earth Leakage Current	<3mA
Ingress Protection (front / rear)	IP43
Controlling system	HD-MPVP2 (DVI,HD-SDI, HDMI, Etc)

**Safety warnings**

1. Please don't install this LED Screen in intense magnetic and high-voltage fields.
2. To reduce the risk of component damage and fire caused by short circuit, make sure correct connection
3. Check if the voltage and power input suit the LED requirement
4. Don't connect cables with power on, make sure a correct connection and no short circuit checked with instrument before power on.
5. Please don't open Receiver cover while still LED still on to avoid risk.

**Dimensions**